

M-ADSL-PCI-C

Dynamode Internal PCI (Conexant) ADSL Modem



FEATURES

- ▶ Compliant with ADSL standards
 - Full-rate ANSI T1.413 Issue 2 and ITU Gdmt (G.992.1) standards
 - Splitterless ITU G.lite (G.992.2) specification.
- ▶ DMT modulation and demodulation.
- ▶ Full rate transmission at up to 8 Mbps downstream and 640 Kbps upstream.
- ▶ G.lite Transmission at up to 1.5 Mbps downstream and 512 Kbps upstream.
- ▶ Support PPP over ATM (RFC 2364) and bridged Ethernet over ATM (RFC 1483).

User Interface

- ▶ I/O
 - LINK jack
- ▶ LED Indicators
 - ACT LED
 - LINK LED

Environment

- ▶ Working: 0 C - 40 C
- ▶ Storage: -40 C - 65 C
- ▶ Humidity: 10% - 90%

Minimum System Requirements

- ▶ Pentium MMX233 Mhz or higher(or Compatible)
- ▶ 32 Mbytes memory or more
- ▶ Windows 95 OSR2, NT4.0 SP4, 98, ME, 2000, XP
- ▶ ADSL service from your telephone company

Regulatory Approvals

- ▶ FCC approved Part 15, Class B
- ▶ FCC approved Part 68
- ▶ UL / CUL Listed