

WL-GI-600SMF

802.11g Wireless PCI Card



PowerBurst™



GREAT FEATURES

- Proven Wireless RT2561 ASIC chipset
- PacketOVERDRIVE™ for enhanced throughput
- 3dBi Antenna
- 802.11g (54Mbps), 802.11b(11Mbps) auto sensing
- PCI 32-Bit Plug n' Play interface
- Safe&Secure™ WPA, WPA-PSK, WPA2, 802.1x
- Legacy Support for WEP 64/128-bit encryption
- Advanced QoS with WMM compatibility
- WiFi and WHQL certified
- Supports: Microsoft® Windows® 98/ME/2000/XP
- Supports: Microsoft® Vista, Linux®, MAC OS X™



SPECIFICATION

ASIC Chipset	Rt2561
Protocols	802.11g (54Mbps) 802.11b (11Mbps), auto-selectable
Interface	PCI 32-bit Card, Plug n' Play
Frequency	2.4 GHz~2.4835 GHz with DSSS and OFDM technology. Adhoc and Infrastructure modes supported
Transmit Distance	Up to 100m* (depending on environmental factors)
Transmit Power	16dBi (approx)
Status LEDs	LINK/ACT
Environment	Operating Temperature: 0 degree C ~ 40 degree C Operating Humidity: 10% ~ 90% RH, non condensing Storage Humidity: 5% ~ 90% RH, non condensing
Operating Systems	Microsoft® Windows® 98/SE/ME/2000 Microsoft® Windows® Vista® Linux® MAC OS X®
Conformance	CE, FCC, RoHS, WiFi

© 2011 Dynamode
Details correct at going to press. E&OE
All Trademarks Acknowledged